

**VLMT.EX2534****Special System Water Control Valves, Pressure-reducing and Pressure-control Type**
[Page Bottom](#)
Special System Water Control Valves, Pressure-reducing and Pressure-control Type
[See General Information for Special System Water Control Valves, Pressure-reducing and Pressure-control Type](#)
GRISWOLD INDUSTRIES, DBA CLA-VAL CO

EX2534

1701 PLACENTIA AVE
COSTA MESA, CA 92627-4416 USA

"Clayton", pilot operated pressure control valves, iron iron body, (sizes 1-1/2 to 8 in.), ductile iron body (sizes 1-1/2 to 8 in) and bronze body (sizes 1-1/2 to 3 in.) consisting of the following models, sizes, inlet pressure ratings, and outlet pressure setting ranges:

Model	Size In.	Max Rated Inlet Pressure psig	Outlet Pressure Setting Range psig
90G-21	1-1/2 to 8	175	30-165
90A-21	2 to 6	175	30-165

"Clayton", pilot operated pressure control valves, steel body, (sizes 1-1/2 to 6 in.) ductile iron body (1-1/2 to 6 in.) and bronze body (sizes 1-1/2 to 3 in.) consisting of the following models, sizes, inlet pressure ratings, and outlet pressure setting ranges:

Model	Size In.	Max Rated Inlet Pressure psig	Outlet Pressure Setting Range psig
90G-21	1-1/2 to 8	300	30-165
90A-21	1-1/2 to 8	300	30-165

For all valves, the manufacturer's design and installation instructions include a description of the performance characteristics for both flow and static conditions.

[Last Updated](#) on 2008-07-03

[Questions?](#)
[Print this page](#)
[Terms of Use](#)
[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".