



HLXS.EX4887 Butterfly Valves

[Page Bottom](#)

Butterfly Valves

[See General Information for Butterfly Valves](#)

GLOBAL SAFETY PRODUCTS INC

EX4887

970 E ORANGETHORPE AVE STE B
ANAHEIM, CA 92801-1132 USA

Model BB-G, bronze body, grooved-ends, sizes 2 and 2-1/2 in. for a rated pressure of 175 psi.

Model BB-T, bronze body, threaded ends, sizes 1, 1-1/4, 1-1/2, 2 and 2-1/2 in. for a rated pressure of 175 psi.

The Models BB-G, BB-T valves may be provided with factory installed supervisory tamper switches intended for indoor use only.

Model BV-G, sizes 2-1/2, 3, 4, 6 and 8 in., groove end type.

Model BV-W, sizes 2-1/2, 3, 4, 6 and 8 in., wafer type. These valves may be provided with factory installed supervisory tamper switches for indoor use only.

These valves are rated for pressures not exceeding 175 psi.

Model BO-G 300, sizes 2-1/2, 3, 4, 6 and 8 in.; DN65, DN80, DN100, DN150, DN200; groove end type.

Model BO-W 300, sizes 2-1/2, 3, 4, 6 and 8 in.; DN65, DN80, DN100, DN150, DN200; wafer type. Model BO-G 300, BO-W 300, valves are rated for pressures not exceeding 300 psig.

BO-G 300, BO-W 300 valves may be provided with factory installed supervisory tamper switches for indoor or outdoor use.

Model	Size, NPS	Body Type	Pressure Rating, psig (Bar)	Indicator Post	Supervisory Switch*
Butterfly valve					
HPBO-W	2-1/2, 3, 4, 6 and 8	Wafer	300 (20.7)	—	I, O
HPBO-W	10	Wafer	175 (12)	—	I, O
BVG1	2-1/2, 3, 4 and 6	Grooved	175 (12)	—	I, O
BVW1	2-1/2, 3, 4 and 6	Wafer	175 (12)	—	I, O
BOG310	2-1/2, 3, 4 and 6	Grooved	300 (20.7)	—	I, O
BOW310	2-1/2, 3, 4 and 6	Wafer	300 (20.7)	—	I, O
HPBOW1	2-1/2, 3, 4 and 6	Wafer	300 (20.7)	—	I, O

* I = Indoor installation; O = Outdoor installation

[Last Updated](#) on 2015-05-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".